

W6 Connect Splitter v.1.0.0.

Technical Data

Housing dimensions (HxWxD)	120 x 101 x 23 mm
Housing type	DIN rail housing (for DIN rail version EN 60715)
Housing material	Self-extinguishing blend PC/ABS
Weight	approx. 200 g
Protection class	IP20
Power supply	12-24 V DC -15 % / +20 %
Max. power consumption	5 W
Operating temperature	-25 °C to +55 °C
Storage temperature	-40 °C to +85 °C
Humidity (40 °C)	up to 93 % (non-condensing)
Interfaces	- 1xRS232; - 2xRS485
Connectors	1 x 3 pole screw-type terminal for power supply
Processor cooling	Passive with heat sink
Optical indicator	- 1 Green LED for Master regular communication - 1 Yellow LED for RS485 0 regular communication - 1 Green LED for RS485 1 regular communication
Conformity	CE, RoHS
Lifetime	December 2026

WARNINGS

- This product should be operated in a well-ventilated environment, and if used inside a case, the case should not be covered.
- Whilst in use, this product should be placed on a stable, flat, non-conductive surface, and should not be contacted by conductive items.
- The connection of incompatible devices to the device may affect compliance, result in damage to the unit, and invalidate the warranty.
- All peripherals used with this product should comply with relevant standards for the country of use and be marked accordingly to ensure that safety and performance requirements are met.
- The cables and connectors of all peripherals used with this product must have adequate insulation so that relevant safety requirements are met.

SAFETY INSTRUCTIONS

To avoid malfunction or damage to this product, please observe the following:

- Do not expose to water or moisture, or place on a conductive surface whilst in operation.
- Do not expose to heat from any source; the device is designed for reliable operation at normal ambient temperatures.
- Take care whilst handling to avoid mechanical or electrical damage to the printed circuit board and connectors.
- Whilst it is powered, avoid handling the printed circuit board, or only handle it by the edges to minimise the risk of electrostatic discharge damage.